




Fork positioner

RZV-G-SF-S-L-SE
RZV-G-SF-PC

integral sideshift, bolt-on forks

The **fork positioner RZV-G** has a stable round bar guide in which the carrier with bolt-on forks is positioned. Integral sideshift enables sideshifting dependent on opening range of the forks. Use of standard forks according to ISO 2328 is also possible.



SideCam + Laser + Secure

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x L mm	V LLC mm	ESP COG mm	weight kg
RZV 16-G-SF-S-L-SE*	1600/500	1,0-1,6/500	II	980	470-1040	100x40x1200	126	228	220
RZV 20-G-SF-S-L-SE*	2000/500	1,8-2,0/500	II	1040	470-1100	100x45x1200	126	221	232
RZV 25-G-SF-S-L-SE*	2500/500	2,5/500	II	1150	490-1230	120x40x1200	126	215	252
RZV 28-G-SF-S-L-SE*	2500/600	2,5/600	II	1150	495-1235	125x45x1200	126	225	275
RZV 30-G-SF-S-L-SE*	3000/500	3,0/500	III	1150	495-1235	125x45x1200	138	205	305
RZV 35-G-SF-S-L-SE	3500/500	3,0/600- 3,5/500	III	1150	490-1230	140x50x1200	138	222	345
RZV 40-G-SF-S-L-SE	4000/500	3,5/600- 4,0/500	III	1350	490-1430	140x50x1200	153	225	400
RZV 45-G-SF-S-L-SE	5000/600	4,0-5/600	III	1350	500-1440	150x60x1200	153	225	450

PremiumCam (FrontCam and SideCam)

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x L mm	V LLC mm	ESP COG mm	weight kg
RZV 16-G-SF-PC*	1600/500	1,0-1,6/500	II	980	470-1040	100x40x1200	126	228	220
RZV 20-G-SF-PC*	2000/500	1,8-2,0/500	II	1040	470-1100	100x45x1200	126	221	232
RZV 25-G-SF-PC*	2500/500	2,5/500	II	1150	490-1230	120x40x1200	126	215	252
RZV 28-G-SF-PC*	2500/600	2,5/600	II	1150	495-1235	125x45x1200	126	225	275
RZV 30-G-SF-PC*	3000/500	3,0/500	III	1150	495-1235	125x45x1200	138	205	305
RZV 35-G-SF-PC	3500/500	3,0/600- 3,5/500	III	1150	490-1230	140x50x1200	138	222	345
RZV 40-G-SF-PC	4000/500	3,5/600- 4,0/500	III	1350	490-1430	140x50x1200	153	225	400
RZV 45-G-SF-PC	5000/600	4,0-5/600	III	1350	500-1440	150x60x1200	153	225	450

- 2 hydraulic functions required
- includes hoses and couplings
- includes 5-pin M12 transfer connector
- integral sideshift as standard
- features bolt-on forks as standard
- plug and play connection as standard
- 12/24 Volt system

- protection strip with integrated hose guide as standard
- suitable for longer forks
- clamping of goods not allowed
- accessories see page 181

*for forks longer than 1600 mm the cross section
might change, please ask