
Quick-change system

manual operation

With the Durwen quick-change unit SWV, attachments can be changed quickly and without the use of tools. This device is suitable when the truck is used for a wide range of applications and several attachments are needed. The lower locking mechanism is manually operated as standard. The fork carriage is hooked into the upper mounting of the base frame.







quick change unit, hook-on base frame							
type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	ESP COG mm	weight kg	
SWV 25	2500/600	2500/600	II	1050	30	105	
SWV 35	3500/600	3500/600	III	1050	32	175	
SWV 45	5000/600	5000/600	III	1050	38	180	
SWV 100	8000/900	8000/900	IV	1100	50	300	

single hook-on fork carriage, for additional ISO forks or attachment							
type	ISO	B mm	weight kg				
fork carriage for SWV 25	II	1050	65				
fork carriage for SWV 35	III	1150	123				
fork carriage for SWV 45	III	1350	150				
fork carriage for SWV 100	IV	1800	350				

 hooks can be welded directly on some Durwen attachments for reduced lost load center and higher residual capacity. SWV 25, SWV 35, SWV 45, SWV 100: upon request, no add-on price for integral attachments - choose from this catalogue. Option available for: PGK, PBK, PZK, USK, UKK (all), ZVP, RZV, PZV, RZV-TGZ, ZVP-TGZ

technical data quick change unit (base frame) incl. fork carrige with hooks					
type	V LLC mm	ESP COG mm	weight kg		
SWV 25 + fork carriage	140	62	170		
SWV 35 + fork carriage	195	85	298		
SWV 45 + fork carriage	205	95	330		
SWV 100 + fork carriage	272	150	650		

constant sideshift upon request (requires one additional hydraulic function)	extra weight kg	extra thinkness mm
constant sideshift ISO II	+20 kg	+17 mm
constant sideshift ISO III	+25 kg	+17 mm
constant sideshift ISO IV	+85 kg	+23 mm

- hydraulic locking upon request
- parking devices for attachments upon request
- integral version upon request
- multiple quick coupling upon request

