
Hydraulic telescopic fork arms



The hydraulic telescopic fork arms TGZ are the ideal solution for many transport and loading applications. Vehicles can be loaded and unloaded from one side. The telescopic forks feature 100% synchronised reach movement for ease of use. This feature further supports excellent visibility and simple installation. Fork pockets feature +2mm wear resistant mangan steel wear zone as standard.



type	capacity kg LC 1 mm	capacity kg LC 2 mm	lift truck to LC mm	ISO	retracted L1/L2 mm	b x h mm	fork back B x V mm	H mm	ESP 1/ESP 2 COG 1/COG 2 mm	weight set kg
2-cylinder model										
TGZ.50.1200 TGZ.50.1350	5000/600	2300/1450 1900/1750	5,0/600	IV	1200/2050 1350/2350	161x62	150x50	1059	375/555 440/655	260 280
TGZ.60.1200 TGZ.60.1350	6000/600	3100/1450 2570/1750	6,0/600	IV	1200/2050 1350/2350	215x69	200x50	1059	390/605 450/720	375 405
TGZ.80.1200 TGZ.80.1350	8000/600	4100/1450 3400/1750	8,0/600	IV	1200/2050 1350/2350	215x79	200x60	1059	395/595 460/700	440 475
4-cylinder model										
TGZ.100.1200* TGZ.100.1350*	10000/600	4600/1450 3800/1750	10,0/600	IV	1200/2050 1350/2350	330x62	320x50	1059	365/550 430/650	555 590

- 1 hydraulic function required
- includes hoses and couplings
- standard with easily replaceable wear zones and fork tip made of solid steel to reduce service costs
- thicker mangan steel wear zone (+6 mm) (ISO IV) upon request
- pallet stop ISO II/III (see page 188) upon request: A) 75 mm on the fork pocket sides
 - B) 400 mm

 - C) 850 mm

type B and C reduce the useable length by 50 mm

- different pallet stop positions upon request
- ISO type B mounting (ISO IV) upon request
- standard colour: dark grey

- low built height TGZ available upon request
 - *consider fork section when choosing pallets or loading scheme

Please note:

- standard load backrest does not fit with TGZ installed.

