


Fork positioner

ZVW-GS
ISO II

constant sideshift, bolt-on forks

The high-performance fork positioner ZVW-GS offers outstanding durability and excellent visibility.

The double chrome axis guideways is particularly clean and enables precise fork positioning due to high-quality hydraulics. The bolt-on forks are firmly attached to the carriers and provide smooth running and precision even in quick operation. The constant sideshift operates at every fork position. This means that a separate cylinder moves the complete frame.





type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm OTO	forks b x h x L mm	sideshift mm	V LLC mm	ESP COG mm	weight kg		
ZVW 16-GS*	1600/500	1,0-1,6/500	II	850 980 1040	300-730 300-860 300-920	100x40x1200	+/- 75 +/- 100 +/- 100	124	222 216 212	273 283 285		
ZVW 20-GS*	2000/500	1,8-2,0/500		850 980 1040 1150	300-730 300-860 300-920 300-1030		100x45x1200		+/- 75 +/- 100 +/- 100 +/- 100	234 232 227 221	285 290 298 309	
ZVW 25-GS*	2500/500	2,5/500		980 1040 1150 1350	320-880 320-940 320-1050 320-1250				120x40x1200	+/- 100	243 238 231 219	305 308 319 341
ZVW 28-GS*	2500/600	2,5/600		1040 1150 1350	325-945 325-1055 325-1255	125x45x1200				+/- 100	256 249 236	328 339 361

- 2 hydraulic functions required
- includes hoses and couplings
- constant sideshift as standard
- features bolt-on forks as standard
- also for hook-on forks ISO 2328
- load backrest/protection strip see page 218
- clamping of goods is not allowed

***Forks longer 1600 mm
cross section changes**

type	forks b x h mm
ZVW 16-GS	120x40
ZVW 20-GS	120x40
ZVW 25-GS	120x50
ZVW 28-GS	125x50



option: protection strip

DURWEN
Forklift Attachments

More than 75 years experience