


Clamp with turnable forks

DDGK

360° endless rotation, no sideshift

The revolving clamp with turnable forks **DDGK** allows for flexible use of forklift trucks. The fork on this attachment can be converted manually from pallet to clamp position. Loads standing close together can be clamped easily. Pallets can also be handled simply with forks in the normal position. The attachment is not recommended for heavy duty clamp jobs and clamping with forks in the pallet position is not allowed.



type	capacity on forks kg LC mm	capacity as clamp kg LC mm	lift truck to LC mm	ISO	B mm	opening range A1 IT1 mm	opening range A2 IT1 mm	forks b x h x L mm	R mm	V LLC mm	ESP COG mm	weight kg
DDGK 20	1800/500	1200/500	1,5-2,0/500	II	1050 1150	130-1210 315-1675	405-1485 590-1950	125x45x1200	105	219	240 235	630 645
DDGK 25	2300/500	1750/500	2,0-2,5/600	II	1050 1150	115-1195 300-1660	395-1475 580-1940	140x50x1200		225	242 239	815 830
DDGK 30	2800/500	2000/500	3,0/500	III	1050 1150 1350	115-1195 300-1660 300-1860	395-1475 580-1940 580-2140	140x50x1200		225	241 238 232	820 835 865

- 2 hydraulic functions required (3 hydraulic functions with constant sideshift)
- includes hoses and couplings
- standard with protection strip type SB-DG (does not rotate, height = H, for exact type see page 216)
- forks can be set to 0°/45°/90°, clamping only in 90° position
- max. fork length 1600 mm
- mounting ISO A as standard, ISO B upon request
- constant sideshift see page 218
- solenoid valve upon request (12 V, 24 V, 48 V, 80 V - please specify)
- hydraulic fork turn upon request
- pressure gauge with hand wheel upon request
- manual 3 stage pressure relief valve upon request



image shows horizontal fork position for pallet handling

image shows vertical fork position for clamping

DURWEN
Forklift Attachments

More than 75 years experience